CIRKAN C

HIGH QUALITY OIL FOR MOVING PARTS
Product Characteristic Sheet

APPLICATIONS

Loss lubrication

- **CIRKAN C** oils are pure mineral oils with appropriate viscosities for loss lubrication of:
  - moving parts
  - swivels
  - journals
  - chains

SPECIFICATIONS

International specifications

- ISO 6743/1 AH
- ISO 6743/4 HH

PROPERTIES

- High natural viscosity index
- Compatible with seals
- High ignition point
- Benefits from advanced refining: almost transparent in appearance.

TYPICAL CHARACTERISTICS

	METHODS	UNITS	CIRKAN C						
			32	**46**	**68**	**100**	**150**	**220**	**320**
Density at 15 °C	ISO 3675	kg/m³	870	877	884	886	890	897	900
Viscosity at 40 °C	ISO 3104	mm²/s	32	46	68	100	150	220	320
Viscosity at 100 °C	ISO 3104	mm²/s	5.7	7.1	9.1	11.3	15.3	19.2	25
Viscosity index	ISO 2909		100	99	97	96	96	96	96
Open cup flash point	ISO 2592	°C	210	230	240	250	260	260	270
Pour point	ISO 3016	°C	- 12	- 12	- 9	- 9	- 9	- 9	- 9

Above characteristics are mean values given as an information.

TOTAL UK Limited
Lubricants Division
Pottery Lane, Ferrybridge, West Yorks,
WF11 8JY

This lubricant used as recommended and for the application for which it has been designed does not present any particular risk.
A material safety data sheet conforming to the regulations in use in the E.C. is obtainable via your commercial adviser.