# DOUBLEFIX INVISIBLE 12 STRIPS

## EXTRA-STRONG, TRANSPARENT DOUBLE-SIDED MOUNTING STRIP




### PRODUCT DESCRIPTION

Extra-strong, entirely transparent double-sided strip for permanently mounting and affixing objects in indoor and outdoor areas. The invisible alternative to screws and nails. Provides a permanent and secure hold on almost all smooth surfaces, e.g. glass, metal, tiles, plastic, painted wood and stone. Ideal for mounting signs, decorative objects, hooks, holders, decorative profiles, thermometers, house numbers, and much more. Also suitable for use in the shower area and for attaching car accessories. UV stable and waterproof.

### FIELD OF APPLICATION

Ideal for mounting signs, decorative objects, hooks, holders, decorative profiles, thermometers, house numbers, etc. on smooth surfaces indoors and outdoors. Suitable for glass, metal, tiles, plastic, painted wood, stone, etc. Also suitable for use in the shower area and for attaching car accessories.
Not suitable for rough surfaces.

### PROPERTIES

· double-sided mounting strip
· extra-strong
· entirely transparent
· for smooth surfaces
· for indoors and outdoors
· UV stable and waterproof
· extremely temperature resistant
· clean, easy, fast

### PREPARATION

**Working Conditions:** The minimum working temperature is 10°C.
**Surface Requirements:** The surfaces to be glued must be firm, clean, dry, and free of grease and dust.
**Preliminary Surface Treatment:** For best results, first cleanse the surfaces (e.g. with alcohol or white spirit).

### APPLICATION

**Directions for use:**
Stick the product onto the object to be mounted without creating air pockets. Remove the protective film without touching the adhesive. Affix the object to the desired spot and press hard for 5 seconds.
**Stains/residue:** Remove residue with white spirit.
**Points of attention:** Do not touch the adhesive as this reduces adhesive strength.

### TECHNICAL SPECIFICATIONS

| | |
|---|---|
| Carrier type: | Acrylic foam |
| Chemical base: | Acrylic |
| Chemicals resistance: | Very good |
| Colour: | Transparent |
| Holding power: | >168 (1kg) |
| Initial tack: | Extremely high |
| Minimum temperature resistance: | -40 °C |
| Maximum temperature resistance: | 93 °C |
| Moisture resistance: | Very good |
| Peel adhesion: | 29 N/25mm |
| Thickness (mm): | 1 mm |
| UV resistance: | Very good |

### PACK SIZES

Strips: 12 pieces in wallet

### STORAGE CONDITIONS

Store in a dry, cool and frost-free place.

Our advice is based on extensive research and practical experience. However, in view of the large variety of materials and the conditions under which our products are applied, we assume no responsibility for the results obtained and/or any damage caused by the use of the product. Nevertheless, our Service Department is always at your disposal for any advice needed.