Technical Sprays
Lubricating and Multifunctional Oils

Garage Door Lube Spray

Prevents Rust , Corrosion & Squeaking | Quick Drying & Excellent Creeping Ability

Garage Door Lube is especially formulated to help install, maintain and use of your residential and commercial garage door system and loading dock doors. It is quick-drying, high-performance lubricant with a no-mess formula for minimized dust collection.

Advantages:

- High-Performance lubrication for hinges, door tracks, chains, pulleys and latches

- Excellent creeping ability

- Prevents rust, corrosion, sticking and squeaking

- Quick drying, no-mess formula

- Small areas are easy to reach with smart nozzle

Technical data

Odour		Petroleum
Colour		beige
Silicone-free		yes
Minimum shelf life	at room temperature	24 mon.
viscosity of base oil (40 °C)	DIN 51 562	21 mm²/s
viscosity of base oil (+100 °C)	DIN 51 562	4 mm²/s
Temperature resistance		-20°C to +150°C
Compatible with Double Nozzle		yes

Approvals / Guidelines

ISSA Code	53.402.09
IMPA Code	450823

Application

Spray in sufficient quantity onto the part to be treated and allow to react. If necessary, wipe off with a clean cloth. Repeat process as required. Avoid contact with plastic and varnished surfaces.

Storage

Container is pressurised. Protect from direct sunlight and temperatures above +50 °C.

Instructions for use

When using WEICON products, the physical, safety-related, toxicological and ecological data and regulations in our EC safety data sheets (www.weicon.com) must be observed.

Available sizes

Conversion table

(°C x 1.8) + 32 = °F
mm/25.4 = inch
µm/25.4 = mil
N x 0.225 = lb
N/mm² x 145 = psi
MPa x 145 = psi
Nm x 8.851 = lb·in
Nm x 0.738 = lb·ft
Nm x 141.62 = oz·in
mPa·s = cP
N/cm x 0.571 = lb/in
kV/mm x 25.4 = V/mil

To the product detail page:

Note
The specifications and recommendations given in this technical data sheet must not be seen as guaranteed product characteristics. They are based on our laboratory tests and on practical experience. Since individual application conditions are beyond our knowledge, control and responsibility, this information is provided without any obligation. We do guarantee the continuously high quality of our products. However, own adequate laboratory and practical tests to find out if the product in question meets the requested properties are recommended. A claim cannot be derived from them. The user bears the only responsibility for non-appropriate or other than specified applications.

WEICON Middle East L.L.C.
United Arab Emirates
phone +971 4 880 25 05
info@weicon.ae

WEICON Czech Republic s.r.o.
Czech Republic
phone +42 (0) 417 533 013
info@weicon.cz

WEICON GmbH & Co. KG
(Headquaters) Germany
phone +49 (0) 251 9322 0
info@weicon.de

WEICON Romania SRL
Romania
phone +40 (0) 3 65 730 763
office@weicon.com

WEICON South East Asia Pte Ltd
Singapore
Phone (+65) 6710 7671
info@weicon.com.sg

WEICON Colombia S.A.S
Colombia
Phone: +57 314 793 86 06
Email: info@weicon.co

WEICON Inc.
Canada
phone +1 877 620 8889
info@weicon.ca

WEICON Ibérica S.L.
Spain
phone +34 (0) 914 7997 34
info@weicon.es

WEICON Italia S.r.L.
Italy
phone +39 (0) 010 2924 871
info@weicon.it

WEICON SA (Pty) Ltd
South Africa
phone +27 (0) 21 709 0088
info@weicon.co.za

WEICON Kimya Sanayi Tic. Ltd. Şti.
Türkiye
phone +90 (0) 212 465 33 65
info@weicon.com.tr